



CHEMICAL PRODUCTS

| Part # | Description |
|------------------------|---|
| FIRE BLOCK | RECTOR SEAL RS 136-FIRE BLOCK, UL APPROVED, ASTM E 136 |
| FIRE STOP 814 | FIRE STOP COMMERCIAL FIRE STOPPING SEALANT, UL APPROVED |
| BUSTER | PENETRATING LUBRICANT, DEMOISTRANT, PROTECTANT 15oz SPRAY |
| K07096 | PAINT WAND WITH INVERTED TIP |
| S03630 | GREEN UPSIDE DOWN MARKING PAINT 20oz |
| S03650 | RED/ORANGE UPSIDE DOWN MARKING PAINT 20oz |
| S03901 | WHITE UPSIDE DOWN MARKING PAINT 20oz |
| S03801 | YELLOW UPSIDE DOWN MARKING PAINT 20oz |
| S03911 | RED UPSIDE DOWN MARKING PAINT 20oz |
| NOOX-X 4 | ANTI OX 4oz BOTTLE |
| NOOX-X 8 | ANTI OX 8oz BOTTLE |
| POLY-X QUART | LUBE QUART BOTTLE |
| POLY-X GALLON | LUBE GALLON TUB |
| POLY-X-5 GALLON | LUBE 5 GALLON BUCKET |
| KINGKAULK | MULTI PURPOSE CAULK 9.8 fl oz |



MANY OTHER ITEMS AVAILABLE AT CES

GOLDEX CABLE LEADS



| Part # | Description |
|--------------|---|
| GX 3000 | USB HUB POWERED 4 X USB PORTS |
| GX 3006 | USB HUB REMOTE POWER 4 X USB PORTS |
| GX 620-06 | USB CABLE 6FT PRINTER TYPE TO USB |
| GX 621-06 | USB CABLE 6FT EXTEND TYPE |
| GXAV DC 06 | SPDIF DIGITAL COAXIAL CABLE—6' RCA TO RCA (SPDIF) |
| GXAVAV LR 06 | CHANNEL AUDIO CABLE-6' DUAL RCA (L&R CHANNEL) |
| GXAV RGB 06P | COMPONANT VIDEO HDTV CABLE-6' TRIPLE RCA TO TRIPLE RCA |
| GXAV SV 06 | S VIDEO CABLE (SVHS) 6' MINI DIN 4 MALE TO MINI DIN 4 MALE |
| GXAV TS 02 | SPDIF DIGITAL OPTICAL CABLE- 2 METER TOSLINK W MINI ADAPTOR |
| GXAV YLR 06P | STANDARD AUDIO & VIDEO KITS-6' 3RCA TO 3RCA COMP VIDEO |
| GXAV YLR 12P | STANDARD AUDIO & VIDEO KITS-12' 3RCA TO 3RCA COMP VIDEO |
| GXDV DD 06 | DIGITAL VIDEO INTERFACE CABLE-6' DVI-D TO DVI-D MALE-MALE |
| GXHD AA 06 | HIGH DEFINITION MULTIMEDIA CABLE-6' HDMI 19PIN TO HDMI 19PIN |
| GXHD DA 06 | HIGH DEFINITION MULTIMEDIA CABLE-6' DVI-D SINGLE LINK TO HDMI 19PIN |
| GXS 712 MC | PREMIUM 8 OUTLET SURGE, COAX, MODEM+ |
| QU4-06 | USB 4 IN 1 CONNECTOR KIT |



CALL CES FOR A FULL LINE CATALOG



ROPE LIGHTS

Please visit us online to see the complete listing at: www.sescatalog.com

| Part # | Description |
|-------------|---|
| ROPE30FT | 30FT UL SEALED ENDS IN BLUE/CLEAR/GREEN/RED/YLLW |
| ROPE50FT | 50FT UL SEALED ENDS IN BLUE/CLEAR/GREEN/RED/YLLW |
| ROPE100FT | 100FT UL SEALED ENDS IN BLUE/CLEAR/GREEN/RED/YLLW |
| ROPEUSA | 30/50/100FT UL APPROVED SEALED ENDS RED-WHITE-BLUE |
| ROPE(COLOR) | 150FT CUTABLE ROLL KITS IN BLU/CLR/GRN/MRN/RED/YLLW |
| ROPE 12V | 150FT CUTABLE ROLL KITS IN CLEAR/GREEN 12 VOLT |
| ROPEPWCORD | POWER CORD 5FT LONG |
| VARIOUS | T CONNECTORS/COUPLINGS/END CAPS/ PWR CONNECTORS/ROPE CLIPS |



BATTERIES

| Part # | Description |
|------------------|---|
| RAYOVAC AL - 9V | RAYOVAC 9V BATTERY |
| RAYOVAC AL - D | RAYOVAC D CELL BATTERY |
| RAYOVAC AL - C | RAYOVAC C CELL BATTERY |
| RAYOVAC AL - AA | RAYOVAC AA CELL BATTERY |
| RAYOVAC AL—AAA | RAYOVAC AAA CELL BATTERY |
| RAYOVAC PS CDN | RAYOVAC MULTI BATTERY CHARGER |
| RAYOVAC NM1604-1 | 9V RECHARGEABLE BATTERY NIMH |
| RAYOVAC NM7 | D/C/AA/AAA CELL RECHARGEABLE BATTERY PACKS NIMH |
| RAYOVAC LD7 | HYBRID AA/AAA CELL RECHARGEABLE BATTERY 4 PACK NIMH |
| RAYOVAC 6V - GP | RAYOVAC 6 VOLT SPRING TOP INDUSTRIAL BATTERY |
| 6V4.5A | EMERGENCY LIGHT BATTERY 6 VOLT 4.5 AMP |



PHASE TAPE



| Part # | Description |
|---------------|--|
| WHITE CW 707P | 3/4" x 60' COLD WEATHER WHITE PHASE TAPE w/PLASTIC CASE - UL |
| BLACK 700P | 3/4" x 66' PREMIUM BLACK PHASE TAPE w/PLASTIC CASE - UL |
| WHITE 700P | 3/4" x 66' PEMIUM WHITE PHASE TAPE w/PLASTIC CASE - UL |

**STRUTS**

| CODE | DESCRIPTION |
|-------------------|--|
| ST12G158X158SLCH | 12 Gage 1 5/8" x 1 5/8" slotted channel |
| ST12G158X158CH | 12 Gage 1 5/8" x 1 5/8" channel galvanized |
| ST12G158X1316SLCH | 12 Gage 1 5/8" x 13/16" slotted channel |
| ST12G158X1316CH | 12 Gage 1 5/8" x 13/16" channel galvanized |
| ST14G158X158SLCH | 14 Gage 1 5/8" x 1 5/8" slotted channel |
| ST14G158X158CH | 14 Gage 1 5/8" x 1 5/8" channel galvanized |
| ST14G158X1316SLCH | 14 Gage 1 5/8" x 13/16" slotted channel |
| ST14G158X1316CH | 14 Gage 1 5/8" x 13/16" channel galvanized |

CHANNEL NUTS**No Spring**

all channel sizes except as noted

| | hole | ht. |
|--------------|----------|-------|
| CNN30031EG | 5/16"-18 | 0.37" |
| CNN30037EG | 3/8"-16 | 0.37" |
| CNN30050EG | 1/2"-13 | 0.37" |
| CNN30062EG | 5/8"-11 | 0.37" |
| CNN30075EG | 3/4"-10 | 0.37" |
| * CNN40087EG | 7/8"-9 | 0.50" |

* Cannot be used with 13/16" & 1" channel

**Top Spring**

for all channel sizes

| | hole | ht. |
|------------|---------|-------|
| CNT20025EG | 1/4"-20 | 0.25" |
| CNT30037EG | 3/8"-16 | 0.37" |
| CNT30050EG | 1/2"-13 | 0.37" |

**Regular Spring**

for 2 3/8" & 1 5/8" channel

| | hole | ht. |
|------------|----------|-------|
| CNR20025EG | 1/4"-20 | 0.25" |
| CNR20031EG | 5/16"-18 | 0.25" |
| CNR30031EG | 5/16"-18 | 0.37" |
| CNR20037EG | 3/8"-16 | 0.25" |
| CNR30037EG | 3/8"-16 | 0.37" |
| CNR30050EG | 1/2"-13 | 0.37" |

**Short Spring**

for 13/16" & 1" channel

| | hole | ht. |
|------------|----------|-------|
| CNS20025EG | 1/4"-20 | 0.25" |
| CNS20031EG | 5/16"-18 | 0.25" |
| CNS30031EG | 5/16"-18 | 0.37" |
| CNS20037EG | 3/8"-1 | 0.25" |
| CNS30037EG | 3/8"-16 | 0.37" |
| CNS30050EG | 1/2"-13 | 0.37" |
| CNS30062EG | 5/8"-11 | 0.37" |

**Long Spring**

for 2 7/16" & 3 1/4" channel

| | hole | ht. |
|------------|---------|-------|
| CNL20025EG | 1/4"-20 | 0.25" |
| CNL30037EG | 3/8"-16 | 0.37" |
| CNL40050EG | 1/2"-13 | 0.50" |

STRUT CLAMPS

*Clamps come in a wide range of sizes.

| CODE | DESCRIPTION | DIMENSIONS |
|-------|-------------------------------|-------------------------|
| LXSCR | Rigid Strut Clamp* | for 1/8"-12" pipe |
| LXSCU | Universal Strut Clamp* | 1/2" - 2" clamp size |
| LXSCE | EMT Strut Clamp* | 1/2" - 2" EMT size |
| LXSCC | Copper Tubing Strut Clamp* | for 1/4" - 6" pipe size |
| LXSCR | O.D. Strut Clamp* | 1/4" - 12 3/4" |
| LXCCT | Cushioned Tubing Strut Clamp* | for 1/4" - 12" tubing |
| LXCCP | Cushioned Pipe Strut Clamp* | 1/2" - 2" clamp |

Please visit www.tamlexusa.com for list of full product range.**FOR MORE INFO, CALL YOUR CES SPECIALIST**



| CODE | DESCRIPTION | DIMENSIONS |
|-------|----------------------------------|-------------|
| TXF10 | Flat Fitting Square Washer | 1/4" bolt |
| TXF31 | Flat Fitting 3 Hole Splice Plate | 5 3/8" bolt |
| TXF32 | Flat Fitting 2 Hole Splice Plate | 7 1/4" bolt |
| TXF33 | Flat Fitting 5 Hole Splice Plate | 9 1/8" bolt |
| TXL10 | Angle Fitting 2 Hole No Twist | 2 1/8" bolt |
| TXL15 | Angle Fitting 2 Hole 3 1/2" | 3 1/2" bolt |
| TXL16 | Angle Fitting 2 Hole 4" | 4" bolt |
| TXL20 | Angle Fitting 2 Hole Cross | 2 1/4" bolt |

Please visit www.tamlexusa.com for list of full product range.

| CODE | DESCRIPTION | DIMENSIONS |
|-------|------------------------------------|------------|
| TXP10 | Single Channel 2 Hole Square | 3 1/2" |
| TXP11 | Single Channel 2 Hole Square Flush | 3 1/2" |
| TXP12 | Single Channel 4 Hole Standard | 1 5/8" |
| TXP13 | Single Channel 4 Hole Standard | 3 1/2" |

| CODE | DESCRIPTION | DIMENSIONS |
|--------|--------------------------------|----------------------------|
| LXBC10 | Formed Steel Standard | 3/4" thickness |
| LXBC30 | Strut to Beam Clamp Z-Type | 3/8" thickness |
| LXBC70 | Strut to Beam Clamp Notch Type | 1/4" thickness |
| LXBC90 | Iron Rod Support Beam Clamp | 1/2" max. flange thickness |

| CODE | DESCRIPTION | DIMENSIONS |
|-------|--------------------------------|------------------------------|
| RDHDG | Stainless - Plain All Threaded | 8' long std., 1/4" - 2" dia. |
| RDB7 | Stainless - Zinc All Threaded | 8' long std., 1/4" - 2" dia. |


Please visit www.tamlexusa.com for list of full product range.

| CODE | DESCRIPTION | DIMENSIONS |
|-------|-----------------------------|------------------------------|
| TBR8R | Shelf Slotted Right | from 6"-30" length |
| TBR8L | Shelf Slotted Left | from 6"-30" length |
| TBR20 | Bracket 3 Hole | 8 1/2" or 10 1/2" length |
| TBR21 | Bracket 6 Hole | 12 1/2" or 14 1/2" length |
| TBR22 | Bracket Brace 6 Hole | 16 1/2", 18 1/2", 20 1/2" L. |
| TBR41 | Bracket Channel Wrap Around | 1 5/8" channel 6" - 12" L. |
| TBR43 | Bracket Channel Notched Up | 6" - 24" lengths |
| TBR45 | Bracket Channel Braced | 12" - 36" lengths |

| CODE | DESCRIPTION |
|------------|---------------------------------|
| ACD60NF-GY | 60 AMP Non-Fusible Pullout 240V |

Please visit www.tamlexusa.com for list of full product range.

FITTINGS



POST BASE



BEAM CLAMPS



THREAD ROD



BRACKETS



DISCONNECT



Levanté

HEATSTORE

visit us @ www.heatstoreusa.com

HAND DRYERS

HD51130



- Hands-free operation
- Metallic construction with aluminum cover and air outlet
- Steel base and propeller
- Adjustable sensor distance
- Over-time safety control automatically switches off after one minute of continuous running
- Safety, overheat cut-off protection
- UL Listed

| | |
|------------------|------------------|
| voltage | 120V/60Hz |
| rated power | 1100W |
| water drip-proof | IPx1 |



HD1588



- Hands-free operation
- Adjustable sensor distance automatically switches off after one minute of continuous running
- Safety, overheat cut-off protection
- ETL Listed

| | |
|------------------|------------------|
| voltage | 120V/60Hz |
| rated power | 1500W |
| water drip-proof | IPx1 |



HD1501



- Hands-free operation
- Metallic construction with aluminum cover and air outlet
- Steel base and propeller
- Adjustable sensor distance
- Over-time safety control automatically switches off after one minute of continuous running
- Safety, overheat cut-off protection
- UL Listed

| | |
|------------------|------------------|
| voltage | 120V/60Hz |
| rated power | 1500W |
| water drip-proof | IPx1 |



CALL CES FOR A FULL LINE CATALOG

HEATSTORE**ADDVENT**visit us @ www.heatstoreusa.com**FANS****SFDC-600T**

- Adjustable tilt head
- Complete metal construction
- 3 speed, high velocity settings
- UL Listed

**18" Tilt Fan****SFDC-600T**

- Slim drum body
- Complete metal construction
- 2 fan speeds
- 120V/60Hz
- Tilting drum body
- 6.5 ft. cord
- UL Listed

**24" Tilt Fan****24" & 30" Industrial Stand Fan**

24" model **SFSI-600S**
 30" model **SFSI-750S**

- Available in 24" or 30"
- Complete metal structure
- 24" model with black guard and aluminum blade
- 120V/60Hz
- 30" model with chrome guard and black blade
- 2 fan speeds and oscillation function
- 6.5 ft. cord
- UL Listed

SEE WEBSITE www.e-ces.net FOR CES LOCATION UP-DATES

**URBAN[®]
TERRAIN****SAFETY
FOOTWEAR*****WORK BOOTS WITH AN ATTITUDE***
...you're looking cool now!**'CHEETAH'****'LEOPARD'****'LYNX'****'PANTHER'****'RHINO'****'SCORPION'*****A Stunning Range Of Fashionable Safety Foot Wear******Six Unique Styles, Sizes 8, 9, 10, 11 & 12*****FOR MORE INFO, CALL YOUR CES SPECIALIST**

**SR-500 & SR-500PS SVRS SWITCHES BY STINGL**

Solid state – Safety Vacuum Release System

Complies with: ASME/ANSI A112.19.17

SR-500PS has two vacuum memory settings, 1 for pool & 1 for spa**Applications:** Works with any size pump (contactor required above 3hp)

- 120v or 240v • Use as stand alone system or in conjunction with any remote system • Includes 24hr electronic timer • Single pump / single pool or spa (SR-500) • Single pump Pool and Spa (SR-500PS)
- Fast easy setup • Battery backup for power failure

The Stingl Switches (SR-500 & SR-500PS) work by monitoring the vacuum on the influent side of the pool or spa pumps 128 times per second. Whenever a blockage occurs in the pool drain or skimmers, the sudden rise in vacuum will cause the Stingl Switch to immediately shut down pump operation and activate an audible alarm. The pump will remain off and the audible alarm will sound until manually reset.

**SS-301-R24 REMOTE ALARM**

24v remote alarm

Provides visual and 85db audible alarm indication

Mounts in any indoor or outdoor location

**E-Stop EMERGENCY STOP SWITCH**

Push-in/pull-out operation provides added layer of protection

Required in some states

May be wired to "low voltage" side of the SVRS switch

**DS-360 Drain Cover**

Anti-entrapment suction outlet safety cover

Fits 5-1/2" to 8" drains (actual size 11")

Complies with: ASME/ANSI A112.19.8 – VGB 2008

Certified flow rate 123 GPM @ 1.5 FPS

- For floor or wall applications • Pool cleaner friendly
- Single or dual drain applications

**DS-360 - 12x12H Drain Cover**

Anti-entrapment suction outlet safety cover

Fits 12"x12" HAYWARD square drains

Complies with: ASME/ANSI A112.19.8 – VGB 2008

Certified flow rate 250 GPM @ 1.5 FPS

- Includes (4) 1/4" shims • Pool cleaner friendly
- Reuse original OEM screws

**DS-360M Drain Cover**

Anti-entrapment suction outlet safety cover

Fits 5-1/2" to 8" drains (actual size 10-3/8")

Also retrofits 5" sumps with additional hardware (order DS-360MA)

Complies with ASME/ANSI A112.19.8 – VGB 2008

Certified flow rate 123 GPM @ 1.5 FPS

- For floor or wall applications • Pool cleaner friendly
- Single or dual drain applications

**DS-360 - 12x12P Drain Cover**

Anti-entrapment suction outlet safety cover

Fits 12"x12" PENTAIR square drains

Complies with: ASME/ANSI A112.19.8 – VGB 2008

Certified flow rate 250 GPM @ 1.5 FPS

- Pool cleaner friendly
- Reuse original OEM screws

DS 9x9
Adapter Plate

DS 360 X

DS Adapter Shims
(for deeper frames)**DS-360X 9"x9" Drain Cover**

Anti-entrapment suction outlet safety cover

Retrofit kit for 9"x9" square drains

Complies with: ASME/ANSI A112.19.8 – VGB 2008

Certified flow rate 160 GPM

- For floor applications only
- Single or dual drain applications

Raychem®

WINTERGARD WET™ PIPE FREEZE PROTECTION OR ROOF & GUTTER DE-ICING

WinterGard Wet™ self-regulating heating cables can be cut-to-length and overlapped without the risk of overheating. This heating cable automatically adjusts its heat output as the ambient temperature changes at each point along its length. Raychem® accessories must be used with Raychem heating cables. UL Listed and CSA Certified. WinterGard Wet is rated 6 watts/ft at 40°F, and has a

waterproof outer jacket which makes this heating cable suitable for use in both wet and dry environments. In addition, it can be used for either pipe freeze protection or roof and gutter de-icing.

WARNING: To minimize the danger of fire if the heating cable is damaged or improperly installed, a ground-fault device (GFPD) must be used.

| Catalog No. | Description | |
|-------------|--|---|
| H612050 | 50 ft Box WinterGard Wet Heating Cable 120 V | |
| H612100 | 100 ft TruckPak® WinterGard Wet Heating Cable 120 V* | |
| H612250 | 250 ft Reel WinterGard Wet Heating Cable 120 V | |
| H6121000 | 1000 ft Reel WinterGard Wet Heating Cable 120 V |  |
| H622050 | 50 ft Box WinterGard Wet Heating Cable 240 V | H612 120 V |
| H622100 | 100 ft TruckPak WinterGard Wet Heating Cable 240 V* |  |
| H622250 | 250 ft Reel WinterGard Wet Heating Cable 240 V | H622 240 V |
| H6221000 | 1000 ft Reel WinterGard Wet Heating Cable 240 V | |

*TruckPaks include 100 ft of WinterGard Wet heating cable, 2 H900 Power Connection Kits, 1 H910 Splice/Tee Kit, and 1 H903 roll of Application Tape.

Raychem Accessory Kits must be used with Raychem heating cables. The H900 Power Connection Kit provides enough materials for one hardwired power connection and includes a gel-filled end seal. The H903 Application Tape is a 66 ft roll but is only needed for pipe freeze protection applications. The H908 Plug-In Power Connection Kit has built-in ground-fault protection and comes with a

gel-filled end seal. The H910 Splice/Tee Kit comes with enough materials for either one splice or one tee, and includes one gel-filled end seal. The H913 and H914 Roof Clips are required when attaching WinterGard Wet to the roof for roof/gutter de-icing. The H915 Downspout Hanger Bracket provides protection when transitioning from the gutter to the downspout.

| Catalog No. | Accessories |
|-------------|--|
| H900 | Hardwire Power Connection Kit with Gel-Filled End Seal |
| H903 | 66 ft Roll Application Tape |
| H908 | Plug-In Power Connection Kit with GFPD and Gel-Filled End Seal |
| H910 | Splice/Tee Kit with Gel-Filled End Seal |
| H912 | Extra Gel-Filled End Seals (2/bag) |
| H913 | Roof Clips (10/bag) |
| H914 | Roof Clips (50/box) |
| H915 | Downspout Hanger Bracket |



www.tycothermal.com

tyco / Thermal Controls

CALL CES FOR A FULL LINE CATALOG

Raychem®

GARDIAN® PREASSEMBLED PIPE FREEZE PROTECTION OR ROOF & GUTTER DE-ICING

Gardian® preassembled self-regulating heating cables require no assembly or thermostat. Available in seven lengths, these cables are 6 watts/ft and come assembled with a 30-inch pigtail cold lead and 3-prong grounded 120 V plug. Plug into a ground-fault protected outlet per the installation

instructions. For length requirements longer than 100 ft, use WinterGard Wet cut-to-length. UL Listed and CSA Certified.

WARNING: To minimize the danger of fire if the heating cable is damaged or improperly installed, a ground-fault device (GFPD) must be used.

| Catalog No. | Description |
|-------------|---|
| W51-6P | 6 ft Preassembled 120 V Heating Cable |
| W51-12P | 12 ft Preassembled 120 V Heating Cable |
| W51-18P | 18 ft Preassembled 120 V Heating Cable |
| W51-24P | 24 ft Preassembled 120 V Heating Cable |
| W51-50P | 50 ft Preassembled 120 V Heating Cable |
| W51-75P | 75 ft Preassembled 120 V Heating Cable |
| W51-100P | 100 ft Preassembled 120 V Heating Cable |



QUICKNET® ELECTRIC FLOOR HEATING SYSTEM

QuickNet® Electric Floor Heating System is easy-to-install under ceramic or natural stone floors. The blue heating cable is secured on to an adhesive-backed red fiberglass mesh that rolls out for fast installation on any type of subfloor. The QuickStat® thermostat is included with each kit and automatically switches the system on or off to maintain preprogrammed or customized heating schedule. Built-in GFCI protection prevents electrical shock.



| Catalog No. | Description |
|----------------|--|
| QuickNet-10-1 | 10 ft ² 120 V Mat with QuickStat Thermostat (20 in x 6.2 ft) |
| QuickNet-20-1 | 20 ft ² 120 V Mat with QuickStat Thermostat (20 in x 12.1 ft) |
| QuickNet-30-1 | 30 ft ² 120 V Mat with QuickStat Thermostat (20 in x 18.4 ft) |
| QuickNet-40-1 | 40 ft ² 120 V Mat with QuickStat Thermostat (20 in x 24.3 ft) |
| QuickNet-50-1 | 50 ft ² 120 V Mat with QuickStat Thermostat (20 in x 30.5 ft) |
| QuickNet-60-1 | 60 ft ² 120 V Mat with QuickStat Thermostat (20 in x 36.4 ft) |
| QuickNet-70-1 | 70 ft ² 120 V Mat with QuickStat Thermostat (20 in x 42.7 ft) |
| QuickNet-80-1 | 80 ft ² 120 V Mat with QuickStat Thermostat (20 in x 48.9 ft) |
| QuickNet-90-1 | 90 ft ² 120 V Mat with QuickStat Thermostat (20 in x 55 ft) |
| QuickNet-100-1 | 100 ft ² 120 V Mat with QuickStat Thermostat (20 in x 61 ft) |
| QuickStat | Digital Programmable Thermostat with Built-In GFCI |
| QuickNet-RK | QuickNet Heating Cable Repair Kit |
| QuickNet-Check | QuickNet Heating Cable Continuity Monitor |

SEE WEBSITE www.e-ces.net FOR CES LOCATION UP-DATES

**Residential****Architectural****Commercial****Industrial**

www.ouellet.com

FOR MORE INFO, CALL YOUR CES SPECIALIST



OUELLET
ELECTRIC HEATING

OTM series
THERMAT Floor Heating System



The comfort of invisible heating

The TherMAT floor heating system provides comfort and well-being through radiant heating. By heating the floor itself instead of the surrounding air, the system provides indirect heat that radiates from the floor up and is absorbed by surrounding objects, warming the entire room. As an integrated heating system, TherMAT produces enveloping heat that is also clean, cost-effective, uniform, and constant. Whether it is used for additional comfort or as a primary heat source, TherMAT is a safe and "green" heating solution that harnesses the benefits of radiant heating, a process that occurs naturally in nature and has long been under-utilized in the industry.

THERMAT Floor Heating System (Width: 16 in.)

| Product # 240V/208V | Product # 120V | Width | | Length | | Covered Surface* | | Watts |
|------------------------|-------------------|-------|------|--------|------|------------------|-------|-------|
| | | in. | m | ft. | m | sq. ft. | sq. m | |
| --- | OTM0082 | 16 | 0.41 | 6' | 1.8 | 8 | 0.7 | 85 |
| --- | OTM0122 | 16 | 0.41 | 7' 9" | 2.4 | 10 | 0.9 | 120 |
| --- | OTM0152 | 16 | 0.41 | 9' 9" | 3.0 | 13 | 1.2 | 150 |
| OTM0170 | OTM0172 | 16 | 0.41 | 11' 3" | 3.4 | 15 | 1.4 | 170 |
| OTM0240 | OTM0242 | 16 | 0.41 | 15' 3" | 4.6 | 20 | 1.9 | 240 |
| OTM0300 | OTM0302 | 16 | 0.41 | 18' 9" | 5.7 | 25 | 2.3 | 300 |
| OTM0360 | OTM0362 | 16 | 0.41 | 22' 6" | 6.9 | 30 | 2.8 | 360 |
| OTM0420 | OTM0422 | 16 | 0.41 | 26' 6" | 8.1 | 35 | 3.3 | 420 |
| OTM0475 | OTM0472 | 16 | 0.41 | 30' | 9.1 | 40 | 3.7 | 475 |
| OTM0600 | OTM0602 | 16 | 0.41 | 37' 6" | 11.4 | 50 | 4.6 | 600 |
| OTM0720 | OTM0722 | 16 | 0.41 | 45' | 13.7 | 60 | 5.6 | 720 |
| OTM0840 | OTM0842 | 16 | 0.41 | 52' 9" | 16.1 | 70 | 6.5 | 840 |
| OTM0960 | OTM0962 | 16 | 0.41 | 60' | 18.3 | 80 | 7.4 | 960 |
| OTM1080 | --- | 16 | 0.41 | 67' 9" | 20.7 | 90 | 8.4 | 1080 |
| OTM1200 | --- | 16 | 0.41 | 75' 3" | 23.0 | 100 | 9.3 | 1200 |
| OTM1440 | --- | 16 | 0.41 | 90' | 27.4 | 120 | 11.1 | 1440 |
| OTM1600 | --- | 16 | 0.41 | 105' | 32.0 | 140 | 13.0 | 1600 |
| OTM1920 | --- | 16 | 0.41 | 120' | 36.6 | 160 | 14.8 | 1920 |

THERMAT Floor Heating System (Width: 32 in.)

| Product # 240V/208V | Product # 120V | Width | | Length | | Covered Surface* | | Watts |
|------------------------|-------------------|-------|------|---------|------|------------------|-------|-------|
| | | in. | m | ft. | m | sq. ft. | sq. m | |
| OTM0840-32 | OTM0842-32 | 32 | 0.82 | 26' 4" | 8.1 | 70 | 6.5 | 840 |
| OTM0960-32 | OTM0962-32 | 32 | 0.82 | 30' | 9.2 | 80 | 7.4 | 960 |
| OTM1080-32 | --- | 32 | 0.82 | 33' 10" | 10.4 | 90 | 8.4 | 1080 |
| OTM1200-32 | --- | 32 | 0.82 | 37' 9" | 11.5 | 100 | 9.3 | 1200 |
| OTM1440-32 | --- | 32 | 0.82 | 45' | 13.7 | 120 | 11.1 | 1440 |
| OTM1600-32 | --- | 32 | 0.82 | 52' 6" | 16 | 140 | 13 | 1600 |
| OTM1920-32 | --- | 32 | 0.82 | 60' | 18.3 | 160 | 14.8 | 1920 |

208V = 78% of output at 240V.
15' floor armor included. 1.5' 6" cold lead.

* Does not represent the surface of the room but rather the covered surface by the floor heating system, excluding the fixtures and other spaces to consider.

www.ouellet.com

MANY OTHER ITEMS AVAILABLE AT CES



Distributed By



CES Now Offers Jar Packaged Fasteners!



- Hold Up Better Than Boxes. No More Boxes Falling Apart Or Torn Lids To Deal With.
- Clear Packaging Allows You To Easily Identify Material.
- New Color Coded Lids By Product Group Allow You To Quickly Identify What You Are Looking For!



Tapping Screws

Self Drill Screws

Machine Screws & Bolts

Nuts

Washers

Electrical Products

Anchors

CALL CES FOR A FULL LINE CATALOG

See Your Local CES Branch For All Your Fastening Needs



Tapping Screws



Self-Drill Screws



Machine Screws



Bolts



Nuts



Washers



Anchor Products



MAKE CES YOUR ONE STOP SHOP FASTENERS

Don't see it in stock? Ask your local CES Branch for any specials you may need. CES has the ability to supply all of your fastening needs, including material in stainless steel, brass & silicone bronze.

SEE WEBSITE www.e-ces.net FOR CES LOCATION UP-DATES